

Technical Data Sheet

Pressure / Temperature / Humidity / Air Velocity / Airflow / Sound level

Gas leak detector

FG 110

KEY POINTS

- Easy to use

or %LEL

- Indication of gas leaking in ppm, %vol
- Hold-min-max function
 - Adjustable back-light

TECHNICAL FEATURES

| Measuring element | semiconductor sensor | | |
|-----------------------|---|--|--|
| Display | 4 lines, LCD technology. Sizes 50 x 36 mm 2 lines of 5 digits with 7 segments (value) 2 lines of 5 digits with 16 segments (unit) | | |
| Probe | Flexible, 330 mm | | |
| Housing | ABS, protection IP54 | | |
| Keypad | 5 keys | | |
| Conformity | Directives CEM 2004/108/CE and NF EN 61010-1 | | |
| Power supply | 4 batteries AAA LR03 1.5 V | | |
| Autonomy | 20 houres | | |
| Ambience | Neutral Gas | | |
| Operating temperature | From 0 to +50 °C | | |
| Storage temperature | From -20 to +80 °C | | |
| Auto shut-off | Adjustable from 0 to 120 min | | |
| Weight | کننده ملزومات برق (^{295 g} | | |

SPECIFICATIONS FUNCTIONS

| Measurement units | Measurement range | Accuracy ¹ | Resolution |
|-------------------|---|-----------------------|-----------------------|
| CH ₄ | | +11-99 | 17 - 77 |
| ppm | From 0 to 10000 | | 1 ppm |
| %vol %LEL | (LPG : 0-1800) From 0 to 1% vol 0 to 20%LEL | 20% of full scale | 0.001%vol D 0.01% LEL |

All the accuracies indicated in this technical datasheet were stated in laboratory conditions, and can be guaranteed for measurements carried out in the same conditions to the conditional conditions of the conditional conditions are conditionally conditional conditions.

%LEL: is the limiting concentrations of gas (in air) that is needed for the gas to ignite and explode.

%VOL: is the limiting concentrations of gas (in air) that is needed for the gas to ignite and explode expressed in percentage of volume in air.

- · Detection of gas such as methane (CH₄), LPG (isopropanol and isobutane) and others combustible gas (hydrocarbons)
- Hold function
- Alarm (from 1000 to 10000 ppm)
- Display of minimum and maximum values
- Configurable auto shut-off
- Backlight



SUPPLIED WITH

Instruments are supplied with:

- Verification certificate
- Transport case (ref : ST 110)



ACCESSORIES

CQ 15 : Magnetic protective housing

MT 51 : ABS transport case



MAINTENANCE

We carry out calibration, adjustment and maintenance of your instruments to guarantee a constant level of quality of your measurements. As part of Quality Assurance Standards, we recommend you to carry out a yearly checking.

GUARANTEE

Instruments have 1-year guarantee for any manufacturing defect (return to our After-Sales Service required for appraisal).

تامین کننده ملزومات برق

الكتريكال - مكانيكال - ابزار دقيق

+Y1-99 1V Y+ TY

www.sazehgostarsgp.com

@sazehgostar_paytakht

www.kimo.fr

Distributed by:



EXPORT DEPARTMENT

Tel: +33. 1. 60. 06. 69. 25 - Fax: +33. 1. 60. 06. 69. 29

e-mail: export@kimo.fr