

DET4TD2 and DET4TR2

Digital Ground Testers



- IP54 rated
- 2, 3 and 4 point testing
- Selectable 25 V or 50 V output
- Dry cell or rechargeable versions
- Simple one button operation
- Robust carry case

DESCRIPTION

Megger's DET4 family of ground testing instruments offers a unique solution to your ground rod and soil resistivity testing needs. The standard instrument comes with, test leads, stakes, terminal adaptors for bare wire, batteries and calibration certificate delivered in a tough polypropylene carry case - everything you need to start testing in one kit.

The ground testers are rated to IP54 making it truly an outdoor instrument. The ground tester has been designed to be easy to use, a large selector switch makes selection of 2 pole, 3 pole or 4 pole test easy with gloved hands - and the design makes the fitting of shorting links to perform 2 pole tests a thing of the past. A large, clear, easy to read LCD display and thumb sized test button again makes the instrument particularly suited to the outdoor conditions of ground testing.

In addition to this ease of use the ground tester also automatically checks the connection and condition of the P spike and the C spike, indicating the status on the display. The instrument also includes a voltmeter to allow you to measure the ground voltage. The ground tester can measure resistance from 0.01 Ω through to 20 k Ω and earth voltages up to 100 V. To allow testing in noisy environments the instrument is capable of rejecting noise of up to 40 V peak to peak.

The DET4TD2 digital ground tester is powered from 8 AA batteries which are widely available and deliver excellent testing time. The DET4TR2 is powered from rechargeable AA cells. The battery charger is built in and the instrument is supplied with an AC/DC adaptor. For both instruments, the battery status is displayed using a bar-graph.

The Megger ground testers comply with stringent safety standards and are rated to 100 V CAT IV. They also have selectable 25 V or 50 V output for compliance with IEC 61557-5.

۰۲۱-۶۶۱۷۲۰۳۲

www.sazehgostarsgp.com

@sazehgostar_paytakht

SPECIFICATIONS

IP rating	IP54	Operating temperature range and humidity	-15 to +55 °C (5 °F to 131 °F)
C stake, P stake and noise check	Automatic	Storage temperature range and humidity	-40 to +70 °C (-40 °F to 158 °F)
Noise rejection	40 V peak to peak	Safety	Complies with the requirements of IEC61010-1 100V CAT IV between terminal pairs.
2 wire, 3 wire, 4 wire test	Yes, no shorting links required		The CAT IV 100 V rating is dependant on the use of a leadset of at least this rating, for example the optional two wire leadset part number 1001-858.
Instrument output	Voltage: ± 25 V or ± 50 V at 94 Hz, 105 Hz, 111 Hz and 128 Hz Current: 4.5 mA or 0.45 mA or 0.045 mA	EMC Compliance	In accordance with IEC61326-1 Complies with the requirements of KEMA K85B.
Resistance range	2, 3, 4 pole: 0.01 Ω to 200 k Ω ART: 0.01 Ω to 200 k Ω Stakeless: 0.01 Ω to 200 Ω		Complies with the following parts of EN61557, "Electrical safety in low voltage distribution systems up to 1000 V a.c. and 1500 V d.c. - Equipment for testing, measuring or monitoring of protective measures".
Maximum probe resistance	Rp limit: 100 k Ω (50 V output voltage) Rc limit: 100 k Ω (50 V output voltage) Limits reduced to 50 k Ω for 25 V output voltage Limits reduced to 5 k Ω for 0.01 Ω resolution		Part 1 - General requirements Part 5 - Resistance to earth
Earth / ground voltage range	0 to 100 V ac	Dimensions	203 mm x 148 mm x 78 mm
Earth / ground voltage accuracy	2% ± 2 V	Weight	1 kg
Display	3 1/2 high contrast liquid crystal, backlit		
Power supply	DET4T2 8 off AA (LR6) cells DET4TR2 8 off AA (LR6) NiMH rechargeable cells Battery charger: 100-240 VAC (50/60Hz)		

سازہ گستر پائتخت

ORDERING INFORMATION

Description	Order Code	Description	Order Code
DET4TD2	DET4TD2	Battery charger (DET4TCR2 only)	6280-370
DET4TR2 (rechargeable)	1000-324	Calibration check box (25 Ohm)	1000-435
Included Accessories		Right angled terminal adaptor set	6220-803
Hard carry case		Black crocodile clip (1)	6220-850
Stake and wire kit (15m, 10m, 3m)		Professional grounding testing kit 2 x 50 m, 2 x 30 m, 4 auger stakes, tape measure, in hard carry case	6320-245
Right angle terminal adaptors (to connect bare wires to terminals)		Vehicle 12 V socket charger (rechargeable versions only)	6280-375
Battery charger (DET4TCR2 only)		'Getting down to earth' A Megger guide to earth testing	21500-072
Accessories		Leadset	1001-858
Replacement hard carry case	5410-429		
2 replacement earth test spikes (200 mm, 8 mm dia.)	6220-804		
Replacement ground test leads (x4) for included kit (15 m, 10 m, 10 m, 3 m)	6220-806		

UK
Archcliffe Road Dover
CT17 9EN England
T +44 (0) 1304 502101
F +44 (0) 1304 207342
UKsales@megger.com

UNITED STATES
4271 Bronze Way
Dallas TX 75237-1019 USA
T 800 723 2861 (USA only)
T +1 214 333 3201
F +1 214 331 7399
USsales@megger.com

OTHER TECHNICAL SALES OFFICES
Valley Forge USA, College Station USA,
Sydney AUSTRALIA, Danderyd SWEDEN,
Ontario CANADA, Trappes FRANCE,
Oberursel GERMANY, Aargau SWITZERLAND,
Kingdom of BAHRAIN, Mumbai INDIA,
Johannesburg SOUTH AFRICA, Chonburi THAILAND

CERTIFICATION ISO
Registered to ISO 9001:2000 Cert. no. Q 09290

DET4TD2_DET4TR2_DS_en_V11
www.megger.com
Megger is a registered trademark